

MATERIAL SAFETY DATA SHEET

RAIN-X® ULTRA WAX (LIQUID)

1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 15587

Version Date: 09/06/02

Product Name: RAIN-X® ULTRA WAX (LIQUID)

Product Use: Wax

Synonyms: RX55616

Company Information

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427
USA

Phone Numbers

Medical Emergency: 1-800-546-6040
Transportation Emergency (USA): 1-800-424-9300
Transportation Emergency (International):
1-703-527-3887 (Call collect)
MSDS Assistance: 1-800-546-6227
Fax On Demand: 1-800-546-6227
Technical Assistance: 1-800-416-1600
Customer Service: 1-800-416-1600
Fax Number: 713-217-3181
Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
SOLVENT NAPHTHA	64742-88-7	10 - 30	Yes
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	< 2	Yes
HEPTANE	142-82-5	< 4	Yes
WATER	7732-18-5	50 - 70	No
POLYDIMETHYLSILOXANE	63148-62-9	< 5	No
SURFACTANTS	MIXTURE	< 5	No

This product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Hazards:

Flammable/Combustible X **Acute Toxin** X **Chronic Toxin** -- **Carcinogen** --
Pressure -- **Reactive** -- **Exposure Limit** X **Target Organ** -- **Other** --

Other: No information available

3. HAZARDS IDENTIFICATION

Emergency and Hazards Overview

CAUTION: FLAMMABLE.

NFPA Ratings: Health 2 Flammability 3 Reactivity 0

Primary Route of Exposure: Skin X Inhalation -- Eye --

Health Effect Information

Eye Contact: Avoid eye contact. May be irritating to the eyes upon direct contact.

Skin Contact: Avoid prolonged and repeated skin contact. Prolonged or repeated contact may result in slight skin irritation.

Inhalation: This product is not expected to pose an inhalation hazard under conditions of foreseeable use.

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 2 of 7

Ingestion: This product is regarded as having a low order of toxicity. If biphasic separation of this mixture occurs, the solvent phase may pose a hazard upon aspiration.

Medical Conditions Aggravated by Exposure: None expected.

Other: No information available

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention.

Inhalation: This material does not present any known inhalation hazard. No treatment is necessary under ordinary circumstances.

Ingestion: No treatment is necessary under ordinary circumstances. Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. If victim exhibits signs of lung aspiration such as coughing or choking, seek immediate medical assistance.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: 72 F, 22.2 C

Test Method: ASTM D-56 (T.C.C.)

Flammable Limits in Air

Upper Percent: No data available

Lower Percent: No data available

Autoignition Temperature: No data available

Test Method: No information available

NFPA Classification: Class IB - flammable liquid

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture.

Unusual Fire and Explosion Conditions: Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: No information available

Other: No information available

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Provide adequate ventilation during clean-up. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10.

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 3 of 7

Regulatory Notifications: No notification required

Containment and Clean up: No special cleanup procedures are necessary.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: No special handling procedures are necessary.

Storage: Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials. Do not transfer to unmarked containers.

Empty Container Warnings

Drums: Not applicable

Plastic: Do not reuse this container. Empty container may retain product residues.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

Component	CAS No.	Exposure Limit
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	OSHA - PEL: TWA 500 ppm ACGIH - TLV: TWA 100 ppm
HEPTANE	142-82-5	OSHA - PEL: TWA 500 ppm ACGIH - TLV: TWA 400 ppm ACGIH - TLV: STEL 500 ppm

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use.

Skin Protection: Skin protection is not required under conditions of normal use.

Respiratory Protection: Respiratory protection is not required under conditions of normal use.

Personal Hygiene: Always wash hands and face with soap and water before eating, drinking, or smoking. Consumption of food and beverage should be avoided in work areas where this product is present.

Engineering Controls / Work Practices

Ventilation: General room ventilation is normally sufficient.

Other: No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 4 of 7

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow opaque	
Odor: Mild	Vapor Pressure: No data available
Physical state: Liquid	Vapor Density (air=1): No data available
pH: Not applicable	Percent Volatile by Volume: No data available
Boiling Point: 140 F, 60 C	Volatile Organic Content: No data available
Melting Point: Not applicable	Molecular Weight: No data available
Specific Gravity: 0.95	Average Carbon Number: No data available
Pour Point: No data available	Viscosity @ 100 F: > 100 SUS
	Viscosity @ 40 C: No data available
Solubility in Water: Partially soluble in water	
Octanol / Water Coefficient: Log K_{ow} = No data available	

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: Keep away from heat, sparks, open flames and other ignition sources.

Incompatible Materials to Avoid: Strong oxidizers, strong acids. Strong bases.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: No information available

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 5 of 7

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): NOT APPLICABLE

Highway / Rail (Non-Bulk): CONSUMER COMMODITY, ORM-D

For US shipments, US DOT law requires the shipper to determine the proper shipping description of the material that is being shipped. The shipping information and description contained in this section may not be suitable for all shipments of this material, but may help the shipper determine the proper shipping description for a particular shipment.

International Information

Vessel: IMDG Regulated: X IMDG Not Regulated: --

Air: ICAO Regulated: X ICAO Not Regulated: --

Other: No information available

15. Regulatory Information

Regulatory Lists Searched: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCM, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 6 of 7

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA, 85 - China Inventory

Regulatory Search Results:

HEAVY AROMATIC SOLVENT NAPHTHA: 50, 80, 81, 83, 84, 85

HEPTANE: 15, 16, 17, 23, 50, 61, 63, 65, 66, 67, 69, 80, 81, 82, 83, 84, 85

POLYDIMETHYLSILOXANE: 80, 82, 83, 84, 85

SOLVENT NAPHTHA: 50, 80, 81, 83, 84, 85

WATER: 80, 81, 83, 84, 85

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.

IARC: No information available

SARA 311 / 312 Categories

Acute: X **Chronic:** -- **Fire:** X **Pressure:** -- **Reactive:** --

Not Regulated: --

Canadian WHMIS Classification

Class B - Flammable and Combustible Material, Division 2, Flammable Liquids

Class D - Poisonous and infectious material, Division 2B, Toxic Material

European Union Classification

Hazard Symbols:

Harmful / Xn / X in square.

Dangerous for the environment / N / dead tree and fish in square

Risk Phrases:

R10: Flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety Phrases:

S2: Keep out of the reach of Children.

S23: Do not breathe gas/fumes/vapour/spray.

S24/25: Avoid contact with skin and eyes.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheet.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

Front Label:

WARNING: FLAMMABLE.

Read carefully other cautions on back.

MATERIAL SAFETY DATA SHEET

MSDS Number: 15587

RAIN-X® ULTRA WAX (LIQUID)

Page 7 of 7

Back Label:

WARNING: Contains petroleum solvents. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES: Keep away from heat, flame, sparks and other ignition sources. Avoid breathing of vapors. Use only in well ventilated areas. Store and transfer in closed, upright position. Avoid contact with eyes. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. For contact with skin or eyes wash thoroughly with water.

KEEP OUT OF REACH OF CHILDREN

MSDS Revisions

Previous Version Date: 09/06/02

Previous Version Information

Section 14 - Transportation Information Revised.

Other

No information available

Prepared By:

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4453 USA

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, SOPUS Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.